

LCD 17" KVM 16 ports w/LAN Connection

מק"ט: KVM16-LAN-17M



תיאור המוצר

Description:

17" LCD KVM Console in 16 Ports w/LAN Connection

Front LCD Console (keyboard, mouse, monitor 17") + KVM Module design 16ports

It's very flexible and convenient for combination;

IP optional (IP card could be installed inside KVM module)

Extra prepositive USB mouse interface

Single port length: 462.6mm; Multi-ports length: 611mm

17" LCD Console Specification:

LCD Console "17		Type
Screen, 4:3 "17	Ratio	LCD Monitor
SXGATFT-LCD	Video	
(H) x 270.336(V)337.920	Visible Square	
60HZ@ 1024*1280	(Resolution (Max	
(16.7M (RGB 6 bit + Hi_FRC	Support Color	
(Typ) 1 : 1000	Contrast	
LED	Backlight	
0.264x0.297mm	Pixel Pitch	
hours 100,000	LEDMTBF	
12V	Input power	
(100Keys, detachable (9 different languages for choose	Keyboard	
Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10	Compatible IBM/AT	
Standard PS/2; USB	Port	
Times 1,000,000<	Using life	Mouse
Touch Screen	Type	
Standard PS/2	Port	
(1000dots/inch, (40x40/mm<	X/Y Resolution	
Times 1,000,000<	Using life	
45mm*445*407	Installation Dimension	
6.15kg	Weight	

KVM Specification:

Port 16		Type
KVM16-LAN-17M		Model
16	Direct Connects	Computer Connection
256	Maximum Connects	
(OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional	CPU Port Selection	
DB 37PIN	Console Connector	
x VGA DB15 Female Blue, 16 x USB 16 OR 16 x PS/2	Monitor, Keyboard/Mouse Switch Module	PC Connector
x RJ45 16	Switch Module Port	
x DC Jack 1	Power	
x RJ45 1	Network Port	
KVM Operation Panel Digital keys	Connection Port Selection	
KVM Operation Panel Function Keys	KVM Reset	
x semi-embedded key 1	IP Module Reset	
x semi-embedded key 1	IP Module Default	
Nixie Tube LED Display	Selected	
x Red 16	Online	
x Green, 1 x Orange 1	IP Network	
USB, PS/2	Keyboard/Mouse	
x 1200 @ 60HZ Local & Remote 1920	(Resolution (Max	
		Analog Mode
		Connectors
		Switch
		LED's

(60s (3s by default ,40 ,30 ,20 ,15 ,10 ,5 ,3	Scan time interval	
C°10-50-	Operating temperature	Operating Environment
C°20-60-	Storage temperature	
0-80%RH, No Condensation	Humidity	
Metal	Housing	Physical Properties
45mm*445*148.4	Dimension	
3.80kg	Weight	