

# HDMI LCD KVM Switch 16 Ports "17

מק"ט: KVM16-HD



## תיאור המוצר

### LCD Monitor Features:

- Front LCD Console (keyboard, mouse, monitor 17") + 16 port HDMI KVM - very flexible and convenient for combination.

- Keyboard is with demountable design, with 9 different languages:

American, English, German, French, Spanish, Swiss, Turkish, Russian, Italian.

- Extra USB mouse interface.

- Support 1080p resolution.

- Total length: 611mm; fit for 800-1200mm cabinet.

## HDMI KVM Module Features:

- Single USB console control 16HDMI interface computer and two additional USB device
- Supports USB TYPE A interface type keyboard and mouse device
- HDMI LCD Console resolution in Optimum:1920x1080@60Hz
- KVM module resolution in Max: 4K@30HZ(3840x2610@30HZ)
- Switch the computer through the front panel buttons, keyboard hotkeys and screen menu (OSD)
- Connect to the controlled device for BIOS-level access without worrying about the risk of viruses and Trojans
- The controlled computer does not need to install any software and drivers, and the controlled computer directly recognizes KVM.
- Upgrade remote network control mode by extending IP BOX
- Support OSD to set user login mode and increase KVM login security requirements
- Support widescreen resolution
- Support DDC communication to adapt to different graphics devices
- Auto scan function monitors all computer operations
- Support for cross-platform operations - Windows, Linux, Mac\*, and Sun\*

## 17" High-Definition Monitor Specification:

Type		17.3" Wide-Screen LCD Console
LCD Monitor	Screen	17.3" Screen, 16:9
	Video	Wide AHVA TFT-LCD
	Visible Square	381.888(H) x 214.812(V)
	Resolution	1920*1080 @60HZ
	Support Color	16.7M RGB 6-bit data+ HiFCR data
	Contrast	600 : 1 (Typ)
	Back light	LED
	Pixel Pitch	0.1989(per one triad) x 0.1989
	LED MTBF	100,000 hours
	Input power	12V
Keyboard (demountable design)	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times
Installation Dimension (mm)		407 x 445 x 45
Weight		8.5kg

## KVM Module Specification:

Type		16Port	
Computer Connection		16	
Port Selection		OSD Menu, Front panel switches, Hot Key	
Connector	Console Connector	Monitor	1 x HDMI Female
		Keyboard	1 x USB Type A Female
		Mouse	1 x USB Type A Female
	PC Connector	Monitor	16 x HDMI Female
		Mouse/Keyboard	16 x USB TYPE B Female
Power	Power Supply	1 x DC Jack	
Key switch	Connection Port Selection	16 x keys	
	KVM Switch Reset	1 x Semi-embedded keys	
LED Instruction	Selected	16 x Green	
	Online	16 x Red	
Simulation Method	Keyboard & Mouse	USB	

Max Resolution Video		4K@30HZ (3840*2610@30HZ)
Scan interval		3, 5, 10, 15, 20, 30, 40, 60 seconds□Default 3 Seconds□
Operating Environment	Operating temperature	0-50°C
	Storage temperature	-20-60°C
	Humidity	0-80%RH□No Condensation
Physical Properties	Housing	metal
	Dimensions (mm)	L 432 x W 155 x H 44
	Product weight:□kgs□	3.88 Kg