

LAN LCD KVM Switch 16 Ports "17

מק"ט: KVM16-LAN-HD



תיאור המוצר

LCD Monitor Features:

- Front LCD Console (keyboard, mouse, monitor 17")
- + 16ports CAT5 KVM - very flexible and convenient for combination.

Support 9 different languages keyboard:

American English, English, German, French, Spanish, Swiss, Turkish, Russian, Spanish.

- IP optional (IP card could be installed inside KVM module).
- Cascade function support.

- With VGA/DVI/HDMI different interface dongles.
- Total length: 611mm, fit for 800-1200mm cabinet.

17" LCD Console Specification:

Type		17" LCD Console
LCD Monitor	Screen	17" Screen, 4:3
	Video	SXGATFT-LCD
	Visible Square	337.920(H) × 270.336(V)
	Resolution	1280*1024@60HZ(Optimum)/1920*1200@60HZ(Max)
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	Contrast	1000 : 1 (Typ)
	Backlight	LED
	Pixel Pitch	0.264x0.297mm
	LEDMTBF	100,000 hours
	Input power	12V
Keyboard (demountable design)	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times
Installation Dimension (mm)		407 x 445 x 45
Weight		6.15kg

KVM Module Specification:

Computer Connection	Direct Connects		16
	Maximum Connects		256
CPU Port Selection			OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)
Connectors	Console Connector		DB 37PIN
	PC Connector	Monitor, Keyboard/Mouse Switch Module	16 x VGA /DVI/HDMI, 16 x USB OR 16 x PS/2
		Switch Module Port	16 x RJ45
	Power		1 x DC Jack
	Network Port		1 x RJ45 (Optional)
Key Switch	Connection Port Selection		KVM Operation Panel Digital keys
	KVM Reset		KVM Operation Panel Function Keys
	IP Module Reset		1 x semi-embedded key
	IP Module Default		1 x semi-embedded key
LED's	Selected		Nixie Tube LED Display
	Online		16 x Red
	IP Network		1 x Green, 1 x Orange
Analog Mode	Keyboard / Mouse		USB, PS/2
Resolution (Max)			1920 x 1200 @ 60HZ Local & Remote
Scan time interval			3, 5, 10, 15, 20, 30, 40, 60s (3s by default)
Operating Environment	Operating temperature		-10-50°C
	Storage temperature		-20-60°C
	Humidity		0-80%RH, No Condensation
Physical Properties	Housing		Metal
	Dimension (mm)		148.4 x 445 x 45
	Weight		