

LCD 17" KVM 16 port w/VGA Connection

מק"ט: HI-KVM16-17M



תיאור המוצר

Description:

17" LCD KVM 16 Port with VGA Connection PS/2 / USB

Front LCD Console (keyboard, mouse, monitor 17") + KVM Module design (1/4/8/16ports); It's very flexible and convenient for combination;

IP optional (IP card could be installed inside KVM module);

Extra prepositive USB mouse interface;

Single port length: 462.6mm; Multi-ports length: 611mm

17" LCD Console Specification:

LCD Console "17		Type	
Screen, 4:3 "17	Ratio	LCD Monitor	
SXGATFT-LCD	Video		
(H) × 270.336(V)337.920	Visible Square		
60HZ@ 1024*1280	(Resolution (Max		
(16.7M (RGB 6 bit + Hi_FRC	Support Color		
(Typ) 1 : 1000	Contrast		
LED	Backlight		
0.264x0.297mm	Pixel Pitch		
hours 100,000	LEDMTBF		
12V	Input power		
(100Keys, detachable (9 different languages for choose	Keyboard	(Keyboard (demountable design	
Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10	Compatible IBM/AT		
Standard PS/2; USB	Port		
Times 1,000,000<	Using life	Mouse	
Touch Screen	Type		
Standard PS/2	Port		
(1000dots/inch, (40x40/mm<	X/Y Resolution		
Times 1,000,000<	Using life		
45mm*445*407		Installation Dimension	
6.15kg		Weight	

KVM Specification:

Port 16		Type	
AS-7116ULS	Model		
16	Direct Connects	Computer Connection	
256	Maximum Connects		
(OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional	CPU Port Selection		
DB 37PIN	Console Connector		Connectors
x VGA DB15, Female Blue 16	Monitor, Keyboard/Mouse Switch Module	PC Connector	
x DC Jack 1	Power		
x RJ45 1	Network Port		
KVM Operation Panel Digital keys	Connection Port Selection		
KVM Operation Panel Function Keys	KVM Reset		
x semi-embedded key 1	IP Module Reset		
x semi-embedded key 1	IP Module Default		
Nixie Tube Display	Selected		
x Red 16	Online		
x Green, 1 x Orange 1	IP Network		
USB, PS/2	Keyboard/Mouse		Analog Mode
x 1200 @ 60HZ Local & Remote 1920	(Resolution (Max		
(60s (3s by default ,40 ,30 ,20 ,15 ,10 ,5 ,3	Scan time interval		

C°10-50-	Operating temperature	Operating Environment
C°20-60-	Storage temperature	
0-80%RH, No Condensation	Humidity	
Metal	Housing	Physical Properties
45mm*445*148.4	Dimension	
4.96kg	Weight	