

Gold Touch 4K HDMI Splitter 8Ports

מק"ט: HDMI-4K-S8



תיאור המוצר

4K*2K HDMI Splitter

Output: 8

Introduction

HDMI-4K-S8 Item belongs to the HDMI signal distribution product.

This is an ultra high definition HDMI splitter supporting 3D and 4K*2K resolution. The ultra HD signal can be easily allocated to multiple monitors that support Ultra HD signals.

The front and rear end of this product can connect to splitter, matrix and extender etc. And the picture effect have no degradation and with good stability. When playing HD video without pause, delay and trailing as well as perfectly supports 3D to make you enjoy three-dimensional picture.

It is widely used for video advertising, monitoring, information release, security system, multimedia teaching system, bank, metro, computer room and long distance transmission management etc..

Feature

- HDMI 1.4a input signal split to eight HDMI 1.4a sink devices
- Support Full HD, Full 3D
- Support 4K*2K
- Support CEC
- Support deep color 24bit,30bit, 36bit,48bit
- Support Blue-Ray 24/50/60fs/HD-DVD/xvYCC
- Digital audio format, as DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD/HD (HBR)
- Support signal retiming
- Support input up to 15metres AWG26 HDMI standard cable length,
- output up to 25metres AWG26 cable length
- No loss of quality
- Installs in minutes

	:Specification
HDMI 1.4a	HDMI version
24/50/60fs/1080p/1080i/720p/576p/576i/480p/480i	HDMI resolution
24bit/deep color 30bit,36bit,48bit	Support video color format
(DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD HD(HBR	Support audio format
340MHz	Max bandwidth
10.2Gbps	Max baud rate
(1.5Volts p-p(TTL~0.5	Input/Output TMDS signal
(5Volts p-p (TTL	Input/Output DDC signal
15m AWG26 HDMI standard cable	Input cable distance
25m AWG26 HDMI standard cable≥	Output cable distance
2A	Max working current
Input:AC (50HZ, 60HZ) :100V-240V; Output: DC12V/3A	..Power adapter format
(to +55°C 15-)	Operating Temperature range
(to 90%RH (No Condensation 5	Operating Humidity range