

Digital Audio Converter - 2 Ways

מק"ט: E-BI-AUDIO



תיאור המוצר

Type: GOLD TOUCH Digital Audio Converter - 2 Ways Color: Silver Overview:

The Digital 2 ways audio converter is a Coaxial / Toslink audio converter, compact and convenient. It accepts S/PDIF audio signal input through either Coaxial cable or Toslink cable, and pass the audio signal to both its coaxial and Toslink output ports. With its built-in amplification feature, It can also serve as a repeater of audio signal and double the transmit distance.

Features:

- Supports two-way conversion: Coaxial to Toslink or Toslink to Coaxial.
- Supports amplification of S/PDIF audio and extends the transferring distance, through coaxial or Toslink cables.
- Select one input from Coaxial or Toslink input ports, and send S/PDIF audio signal to both Coaxial and Toslink output ports

c.

- Compact design and easy to install.
- DC 5V power supply

Specifications:

- Input: 1 x Coaxial RCA Jack;1 x Toslink (optical fiber)
- Output: 1 x Coaxial RCA Jack ;1 x Toslink (optical fiber)
- Support audio format: LPCM2.0/DTS/Dolby-AC3
- Sampling frequency: 650nm
- Max baud rate: 16Mbps
- Output distance: $\leq 10\text{m}$ (Use the optical fiber cable loss less the 0.2Db/m)
- Max working current: 100mA
- Power adapter format: DC5V/USB5V
- Power Consumption (Max): 0.5W
- Operating Temperature: 0°C ~ 40°C / 2°F ~ 104°F
- Storage Temperature: 20°C ~ 60°C / -4°F ~ 140°F
- Operating Humidity range: 20 ~ 90% RH (Non-condensing)
- Dimension: 66 x 55 x 20 (mm)
- Weight: 40g

package included:

- Digital audio converter - 2 ways
- USB to Mini-USB power cable
- User manual